

SÉRIE 10A1197A/FGM1197 ROTÂMETROS METÁLICOS

- Tubo de medida borossilicato
- "O" ring BUNA N
- Flutuador aço inox 316
- Corpo aço inox 304
- Escala 10 - 100% do caudal máximo
- Ligações rosca BSP
- Acessório de ligação aço inox 316 Ti



Ligações (BSP)	Capacidade		Tubo	Flutuador
	Água (l/h)	Ar* (Nm ³ /h)		
1/2"	110	3,25	FP-1/2-17-G-10/80	1/2-GSVT-45
	136	4,0	FP-1/2-21-G-10/80	1/2-GSVT-45
	148	4,3	FP-1/2-17-G-10/80	1/2-GSVT-44
	158	4,7	FP-1/2-17-G-10/80	1/2-GSVT-48
	184	5,5	FP-1/2-27-G-10/80	1/2-GSVT-45
	201	6,0	FP-1/2-21-G-10/80	1/2-GSVT-48
	254	7,5	FP-1/2-27-G-10/80	1/2-GSVT-44
	270	8,0	FP-1/2-27-G-10/80	1/2-GSVT-48
3/4"	445	13,2	FP-3/4-21-G-10/80	3/4-GSVT-54
	613	18,3	FP-3/4-27-G-10/80	3/4-GSVT-54
	715	21,3	FP-3/4-21-G-10/80	3/4-GSVT-53
	874	26,0	FP-3/4-27-G-10/80	3/4-GSVT-56
	987	29,5	FP-3/4-27-G-10/80	3/4-GSVT-53
1"	1067	31,8	FP-1-27-G-10/80	1-GSVT-64
	1210	35,9	FP-1-27-G-10/80	1-GSVT-65
	1498	44,3	FP-1-35-G-10/80	1-GSVT-64
	1703	50,8	FP-1-35-G-10/80	1-GSVT-65
	2134	64,0	FP-1-35-G-10/80	1-GSVT-63
	2497	74,0	FP-1-35-G-10/80	1-GSVT-66

*Ar às condições de pressão atmosférica e 0°C